

Maintenance

- Check the tightness of all bolts, screws and wheels before use.
- Store the toy indoors or cover it with a tarp to protect it from the wet weather.
- Clean the toy with a soft, dry cloth.

Specifications

Net Weight 12kg

Maximum Rider Weight 25kg

Incorrect use of this product could cause serious injury or death. Please read the following for information that may reduce your risk of serious injury or death. Check all documentation before use. Some products feature online documentation, please print and keep with the toy. Check product for loose / broken / damaged / missing parts, wear or leaks (if applicable) before each use. Never use a product with loose / broken / damaged / missing parts, wear or leaks (if applicable). The product has been supplied by a general merchandise retailer that may not be familiar with your specific application or your description of the application. Be sure to attain third-party approval for your application from a qualified specialist before use regardless of prior assurances by the retailer or its representatives.

©2026 Little Nation. All rights reserved. Do not reproduce



WARNING

READ THIS MANUAL CAREFULLY BEFORE USE AND KEEP FOR FUTURE REFERENCE – FAILURE TO DO SO MAY RESULT IN INJURY, PROPERTY DAMAGE AND MAY VOID WARRANTY.

TO AVOID SERIOUS INJURY - Adult Supervision is required

This tricycle is not a toy. It is not designed as a stroller to transport children. This product is not a stroller and does not meet the safety requirements for strollers. Do not use as a means of transport. Do not use on or near the road.

Do not use trike when jogging. Use only when walking



LITTLE NATION

The trike pictured in this manual may differ to the actual trike
Please visit the product page at www.littlenation.com.au for updated instructions in greater detail

User Manual

Toddler Trike User Manual

Safety

Read and understand all safety warnings and instructions before assembling or using the Toddler Trike ("toy").



- THIS PRODUCT IS NOT A STROLLER AND DOES NOT MEET THE SAFETY REQUIREMENTS FOR STROLLERS. DO NOT USE AS A MEANS OF TRANSPORT

- Assembly is for adults only. Sharp edges may be present during assembly. Keep small parts away from children during assembly.

- Choking hazard – small parts included. Not suitable for children under 18 months of age.
- Use the toy under adult supervision. Children may acquire the skills required to steer, and control the toy, however they may not have mature judgment skills of an adult. Never let a child use the toy without adult supervision.
- Maximum load capacity = 25kg.
- Please inspect the toy before each use for wear or loose fasteners etc, and tighten as required. Do not use the toy if abnormal conditions such as cracks or breaks exist.
- Do not operate the toy on public streets or roads, near moving vehicles, steep inclines or steps, near swimming pools, or any other potentially dangerous areas.
- The toy is designed for outdoor use only. Do not operate at night, in the dark, on sand or gravel, dirt, grass, uneven or rough ground. Do not operate around water or in the wet.
- This toy must not be overloaded or used to push or pull other objects.
- This toy is suitable for children aged 18 months and up.
- Some parts of the toy may be damaged due to improper operation.
- Do not allow children near or to touch moving parts when the toy is running.
- We recommend the use of an approved safety helmet, knee pads, elbow pads when riding this tricycle.
- Before each use, check all nuts and bolts for tightness.
- Do not run or jog while pushing the trike.

The supervising adult is required to read these instructions carefully and give correct guidelines to the users on how to safely operate the toy. Instruction should include:

- Accelerating, braking, steering.
- Only 1 rider at a time may use the toy.
- Must wear shoes.
- While toy is in operation, do not place hands, feet or any part of the body, clothing or other articles near moving parts.

Connect the steering rod,

12 - Connect the hooked steering rod to the front steering connector,

13 - Connect the other end of the steering rod to the base of the push handle using lock nuts. Ensure that the steering rod does not cross underneath the frame.

If this is the case, loosen the handlebar clamp and rotate the front wheel so the connector is on the correct side of the bike.



Ensure the parent steer rod bracket of the handlebars is on the same side of the trike as the parent steer on the parent handle. If this is not the case, loosen the handlebar clamp and turn the handlebars 180 degrees.

14 - Connect the basket and tighten,



Assembly



Children may be injured by small parts, sharp edges or electrical components when the toy is not assembled. Please do not allow children near parts when unpacking and assembling the toy. • The toy must be assembled by an adult.

- Please visit www.littlenation.com.au and navigate to the product page for updated instructions.
- We have also sent the instructions to you over email.
- To save paper, this manual contains basic instructions only. For instructions in greater detail follow the links above.



- 1- Insert the front wheel assembly through the head tube of main frame
- 2- Place the silver clamp on the top of the tube sticking through the frame
- 3 - Insert the handlebars and tighten the clamp with a spanner. (not provided).



Tighten the clamp with a spanner. Please ensure the clamp is tight and the handlebars do not turn inside the clamp.

Install the wheels

- 4 - Fit the plastic bushing through the inside of the frame axle tube
- 5 - Fit the brake over the outside of the frame axle tube. Ensure the slots and groove inside the brake line up



- 6 - Take an axle, lock nut, and 2 washers. feed the axle through the wheel casing, wheel and brake. Place a washer at either end and tighten using 2 spanners.



Install The Push Handle

- 7 - Fit the base of the handle through the push handle tube on the frame. Keep the plastic bushings in place
- 8 - Connect the Y push handle post to the top of the push handle casing on the frame



Connect the seat

- 10 - Connect the seat using 2 screws. Ensure the phillips head screws are facing down.
- 11 - Attach the seat cover

Connect the Shade Sail

- 12 - Attach the lower shade support bracket using 2 philips head bolts in the mid section and one nut and bolt connecting to the main strut low on the frame.
- 13 - Connect the safety bars to the lower shade support bracket and join the safety bars with the seat cover around the safety bars.
- 14 - Connect the mid shade support using the screw connectors.
- 15 - Attach the shade sail by pushing down. Please note that the shade sail does not require screws. It uses the compression method.